

PAN MIXER

DZ 300V

The perfect design

Available in a stationary or practical mobile model, the DZ 300V opens up new DIEMensions. The special feet and the installed toggle lever mechanism provide safe positioning, and the pneumatic tyres ensure optimum mobility. Even greater convenience is provided by the optionally available hydraulic plate opening.

The drum cladding distinguishes itself thanks to the 5 mm highly wear-resistant steel, and the solid underframe is impressive due to its robustness.

The tried-and-tested satellite agitator made of Hardox steel for a long lifespan is adjustable and guarantees excellent mixing results. It is ideal for use with fine and coarse grained mixtures with a grain size of up to 32 mm. Almost all materials can be mixed using this Diem universal mixing unit without an additional special mixing unit.

Quick drainage is carried out via a segmental valve in the base of the drum.

Our CE-compliant high-performance pan mixers impress thanks to state-of-the-art, extremely robust construction and special safety devices, such as the hinged protective grid with linked limit switch or the drainage protection grid.

	DZ 300V MOBILE	DZ 300V STATIONARY
Item no.	09462	10604
Motor	400 V, 9.00 kW	400 V, 9.00 kW
Gearbox	44 1/min	44 1/min
Drum capacity	490 l	490 l
Mixing amount	300 l	300 l
Overall height ready to be moved	1705 mm	-
Overall height ready for mixing	1795 mm	1785 mm
Overall width	1370 mm	1305 mm
Overall length	2430 mm	1370 mm
Drum diameter	1138 mm	1138 mm
Drum height	500 mm	500 mm
Filling height	1795 mm	1785 mm
Drainage height	740 mm	730 mm
Weight	549 kg	580 kg
Paintwork	RAL 1013	RAL 1013
Tyres	Pneumatic tyres	-
Miscellaneous	Hinged protective grid	Hinged protective grid



CE-compliant